

Canon



CORPORATE SOLUTIONS



**Color
imagerunner®
LBP 5360**

SPECIFICATIONS

MAIN UNIT

Type:	Desktop Color Laser Printer
Printing Method:	Electrophoto Method (Color RAPID Fusing System™)
Developing System:	Dry Dual Component Developing System
Memory:	Standard 128MB RAM Maximum 384MB RAM*
Hard Disk Drive:	Optional 20GB
Network Interface Connections:	Parallel Connector (IEEE1284 Compatible) 10/100Base-TX (RJ-45)
Other Interface:	USB 2.0 Hi-Speed/USB Full-Speed (USB 1.1 Equivalent)
User Interface:	LCD 16 Characters x 1 Line 8 LED Indicators 8 Operation Keys
First-Print Time:	10.1 Seconds (B/W) 10.1 Seconds (Color)
Warm-Up Time:	0 Seconds From Standby, 45 Seconds or Less After Powering On
Printing Speed (B/W, Color):	22/22 ppm (Letter)
CPU:	PowerPC 750CXr (400MHz**)
Command Language:	UFR II, PCL5c
Print Resolution	
UFR II/PCL5c:	600 x 600 dpi 2400 dpi Equivalent x 600 dpi
Engine Resolution:	600 x 600 dpi
Printer Drivers	
UFR II:	Windows® (Windows 2000/XP/ Server 2003, Citrix MetaFrame), Macintosh® (OS 10.2.8 or later)
PCL5c:	Windows (Windows 98/Me/ 2000/XP/Server 2003, Citrix MetaFrame)
Halftone:	256 Gradations (Continuous-Tone)



Paper Sources Standard: 250-Sheet Paper Cassette (20 lb. Bond) 100-Sheet Multi-Purpose Tray Optional: 500-Sheet x Up To One Paper Cassette Maximum: 850 Sheets Paper Sizes Cassettes: Legal, Letter, Executive, Foolscap, Custom Sizes (Width: 5-7/8" to 8-1/2"; Length: 8-3/8" to 8-1/2") Multi-Purpose Tray: Legal, Statement, Letter, Executive, Foolscap, Index Card, Custom Sizes (Width: 3" to 8-1/2"; Length: 5" to 14") and Envelopes Acceptable Paper Weight Cassettes: 17 lb. Bond to 32 lb. Bond Multi-Purpose Tray: 17 lb. Bond to 80 lb. Cover Maximum Paper Size: Legal (216 x 355.6mm) Output Capacity: Approximately 250 Sheets (20 lb. Bond) Paper Output: Face-Down Duplexing: Standard Automatic Trayless Duplexing (Legal, Letter, Foolscap) Dimensions (H x W x D): 17-1/4" x 16-1/4" x 17-7/8" (Main Unit) Installation Space (W x D): 16-1/4" x 27-7/8" (When Multi-Purpose Tray is extended) Weight: Approximately 48.5 lb. (22kg)***	Power Supply: 100V – 127V, 50Hz/60Hz Power Consumption Operating: Approximately 460W (Average) Standby: Approximately 48W (Average) Power Save Mode: Approximately 16W (Average) Plug: NEMA 5-15P Toner (Estimated Yield): Black: 6,000 Images at 5% Coverage [▲] Full Color: 6,000 Images at 5% Coverage [▲] Optional Accessories Paper Feeder Unit PF-93^{▲▲} Paper Sizes: Legal, Letter, Executive, Foolscap, Custom Sizes (Width: 5-7/8" to 8-1/2"; Length: 8-3/8" to 8-1/2") Paper Cassettes Capacity: 500 Sheets (20 lb. Bond) Dimensions (H x W x D): 6-5/8" x 16" x 22-3/8" Weight: Approximately 11 lb. (5.0kg) Other Optional Accessories <ul style="list-style-type: none"> • Hard Disk Kit HD-93 • Expansion RAM ER-128 • Expansion RAM ER-256 <p><small>* One memory slot available for expanding memory. ** The upper limit of the frequency range. *** Excluding the Toner Cartridges. ▲ When printing letter-sized paper at 5% page coverage with the default print density settings. ▲▲ Up to one additional paper cassette can be added.</small></p>
--	--



1-800-OK-CANON
www.usa.canon.com

Canon U.S.A., Inc.
One Canon Plaza
Lake Success, NY 11042

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has determined that these products meet the ENERGY STAR® guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Windows and Windows NT are registered trademarks of Microsoft Corporation in the United States and/or other countries. Macintosh is a registered trademark of Apple Computer, Inc. CANON and IMAGERUNNER are registered trademarks, and the GENUINE logo are trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. IMAGEANYWARE is a trademark of Canon. All other terms and product names may be trademarks or registered trademarks of their respective owners and are hereby acknowledged. Specifications and availability are subject to change without notice. ©2006 Canon U.S.A., Inc. All rights reserved.

